

## 650V 6A Trench and Field Stop IGBT

### DESCRIPTION :

- High ruggedness performance
- Very tight parameter distribution
- Positive  $V_{CE(SAT)}$  temperature coefficient
- High efficiency for motor control
- Excellent current sharing in parallel operation
- RoHS compliant.



### TYPICAL APPLICATIONS :

- Home appliances
- Motor drives
- Fan, Pumps, Vacuum cleaner

TO-252

## IGBT

MAXIMUM RATINGS (Tvj=25°C unless otherwise specified)

Characteristic	Condition	Symbol	Value	Unit
Collector-Emitter Voltage		$V_{CES}$	650	V
Continuous collector current	Tc=25°C Tc=100°C	$I_{C\ nom}$	12 6	A
Pulsed collector current	t <sub>p</sub> limited by Tvjmax	$I_{CM}$	24	A
Gate emitter voltage		$V_{GE}$	±20	V
Short circuit withstand time		t <sub>SC</sub>	10	us
Power dissipation	Tc=25°C Tc=100°C	$P_{tot}$	136 68	W
Temperature under switching conditions		Tvj op	-40~+175	°C
Storage temperature		T <sub>STG</sub>	-55~+150	°C

## THERMAL CHARACTERISTICS

Characteristic	Condition	Symbol	Max.	Unit
IGBT thermal resistance, junction - case		$R_{th(j-C)}$	1.1	K/W
Diode thermal resistance, junction - case		$R_{th(j-C)}$	3.8	K/W
Thermal resistance, junction - ambient		$R_{th(j-A)}$	90	K/W

## ELECTRICAL CHARACTERISTICS

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Collector-emitter cut-off current VCE=650V, VGE=0V Tvj=25°C	$I_{CES}$			10	μA
Gate-emitter leakage current VCE=0V, VGE=20V Tvj=25°C	$I_{GES}$			100	nA
Gate-Emitter threshold voltage IC=1.0mA, VGE= VCE Tvj=25°C	$V_{GE(th)}$	5.2	6.2	7.2	V
Collector-Emitter saturation voltage VGE=15V, IC=6A Tvj=25°C VGE=15V, IC=6A Tvj=175°C	$V_{CE(SAT)}$		1.7 2.2		V
Input capacitance f=1MHz, VCE=30 V, VGE=0 V Tvj=25°C	$C_{ies}$		480		pF
Output capacitance f=1MHz, VCE=30 V, VGE=0 V Tvj=25°C	$C_{oes}$		22		pF
Reverse transfer capacitance f=1MHz, VCE=30 V, VGE=0 V Tvj=25°C	$C_{res}$		8		pF
Gate charge IC = 6A, VGE = 15 V, VCC = 520V Tvj=25°C	$Q_G$		19		nC
Turn-on delay time IC=6A, VCC=400 V Tvj=25°C VGE=0/15 V, RG=10Ω Tvj=175°C (inductive load)	$t_{d(ON)}$		10 11		ns
Rise time IC=6A, VCC=400 V Tvj=25°C VGE=0/15 V, RG=10Ω Tvj=175°C (inductive load)	$t_r$		8 10		ns
Turn-off delay time IC=6A, VCC=400 V Tvj=25°C VGE=0/15 V, RG=10Ω Tvj=175°C (inductive load)	$t_{d(OFF)}$		79 108		ns
Fall time IC=6A, VCC=400 V Tvj=25°C VGE=0/15 V, RG=10Ω Tvj=175°C (inductive load)	$t_f$		56 89		ns
Turn-on energy IC=6A, VCC=400 V Tvj=25°C VGE=0/15 V, RG=10Ω Tvj=175°C (inductive load)	$E_{(ON)}$		0.11 0.16		mJ

Turn-off energy loss per pulse IC=6A, VCC=400 V      Tvj=25°C VGE=0/15 V, RG=10Ω      Tvj=175°C (inductive load)	$E_{(OFF)}$		0.10 0.16		mJ
---	-------------	--	--------------	--	----







## Diode

MAXIMUM RATINGS (Tvj=25°C unless otherwise specified)

Characteristic	Condition	Symbol	Value	Unit
Repetitive peak reverse voltage	Tvj=25°C	$V_{RRM}$	650	V
Continuous forward current	Tc=100°C	$I_F$	6	A
Diode maximum current	$t_p$ limited by Tvj max	$I_{FM}$	24	A

## ELECTRICAL CHARACTERISTICS

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Forward voltage IF=6A, VGE=0 V      Tvj=25°C IF=6A, VGE=0 V      Tvj=175°C	$V_F$		1.6 1.4		V
Reverse Recovered Time IF=6 A,      Tvj=25°C -diF/dt =500A/μs      Tvj=175°C VR=400 V	$T_{rr}$		55 98		ns
Peak reverse recovery current IF=6 A,      Tvj=25°C -diF/dt =500A/μs      Tvj=175°C VR=400 V	$I_{RRM}$		10 12		A
Reverse Recovered charge IF=6 A,      Tvj=25°C -diF/dt =500A/μs      Tvj=175°C VR=400 V	$Q_{rr}$		306 529		nC

Figure 1. Typical output characteristics ( $T_{vj}=25^{\circ}\text{C}$ )Figure 2. Typical output characteristics ( $T_{vj}=175^{\circ}\text{C}$ )Figure 3. Power dissipation as a function of  $T_C$ Figure 4. Typical  $I_F$  as a function of  $V_F$ Figure 5. Typical  $V_{GE(th)}$  as a function of  $T_{vj}$  ( $I_C=1\text{mA}$ )Figure 6. Typical  $V_F$  as a function of  $T_{vj}$




Figure 7. Typical  $V_{CEsat}$  as a function of  $T_{vj}$




Figure 8. Typical Gate charge




Figure 9. Typical switching times as a function of  $I_c$




Figure 10. Typical switching times as a function of  $R_G$




Figure 11. Typical switching energy losses as a function of  $I_c$




Figure 12. Typical switching energy losses as a function of  $R_G$




Figure 13. Typical capacitance as a function of VCE (f=1Mhz, VGE=0V)






Figure 14. Transient thermal impedance of IGBT

• Circuit diagram



• Package outlines : Dimensions in (mm)



DIM	MILLIMETERS	
	MIN	MAX
A	2.10	2.50
A2	0.00	0.10
B	0.66	0.86
B2	5.18	5.48
C	0.40	0.60
C2	0.44	0.58
D	5.90	6.30
E	6.40	6.80
G	4.47	4.67
H	9.50	10.70
L	1.09	1.21
L2	1.35	1.65
V1	Typ.7°	
V2	0°	6°

## Notice

MOSPEC reserves the rights to make changes of the content herein the document anytime without notification. MOSPEC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies. Please refer to MOSPEC website for the last document.

MOSPEC disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially incurred.

Application shown on the herein document are examples of standard use and operation. Customers are responsible for comprehending suitable use in particular applications. MOSPEC makes no representation or warranty that such application will be suitable for the specified use without further testing or modification.

The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by MOSPEC for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of MOSPEC or others.

These MOSPEC products are intended for usage in general electronic equipment. Please make sure to consult with MOSPEC before you use these MOSPEC products in equipment which require specialized quality and/or reliability, and in equipment which could have major impact to the welfare of human life ( atomic energy control, aeronautics , traffic control, combustion control, safety devices etc.)