

HIGH POWER NPN SILICON POWER TRANSISTORS

General-purpose linear amplifiers, series pass regulators and inductive switching Applications.

FEATURES:

* Low Collector-Emitter Saturation Voltage-

$$V_{CE(SAT)} = 4.0 \text{ V (Max.) @ } I_C = 30 \text{ A, } I_B = 6.0 \text{ A -- 2N3771}$$


$$V_{CE(SAT)} = 4.0 \text{ V (Max.) @ } I_C = 20 \text{ A, } I_B = 4.0 \text{ A -- 2N3772}$$

MAXIMUM RATINGS

Characteristic	Symbol	2N3771	2N3772	Unit
Collector-Emitter Voltage	V_{CEO}	40	60	V
Collector-Emitter Voltage	V_{CEX}	50	80	V
Collector-Base Voltage	V_{CBO}	50	100	V
Emitter-Base Voltage	V_{EBO}	5	7	V
Collector Current-Continuous -Peak	I_C I_{CM}	30 30	20 3C	A
Base Current-Continuous -Peak	I_B I_{BM}	7.5 15	5.0 15	A
Total Power Dissipation @ $T_C=25^\circ\text{C}$ Derate above 25°C	P_D	150 0.857		W W/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	T_J, T_{STG}	- 65 to +200		$^\circ\text{C}$

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance Junction to Case	$R_{\theta jc}$	1.17	$^\circ\text{C/W}$




NPN


2N3771

2N3772

**20 AND 30 AMPE
NPN SILICON
POWER TRANSISTORS
40 and 60 VOLTS
150 WATTS**



TO-3



**PIN 1.BASE
2.EMITTER
COLLECTOR(CASE)**

DIM	MILLIMETERS	
	MIN	MAX
A	38.75	39.96
B	19.28	22.23
C	7.96	9.28
D	11.18	12.19
E	25.20	26.67
F	0.92	1.09
G	1.38	1.62
H	29.90	30.40
I	16.64	17.30
J	3.88	4.36
K	10.67	11.18

ELECTRICAL CHARACTERISTICS ($T_c = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

OFF CHARACTERISTICS

Collector - Emitter Sustaining Voltage (1) ($I_c = 200 \text{ mA}$, $I_B = 0$)	2N3771 2N3772	$V_{CE(SUS)}$	40 60	V
Collector - Emitter Sustaining Voltage ($I_c = 0.2 \text{ A}$, $V_{BE(off)} = 1.5 \text{ V}$, $R_{BE} = 100 \text{ Ohms}$)	2N3771 2N3772	$V_{CEX(SUS)}$	50 80	V
Collector Cutoff Current ($V_{CE} = 30 \text{ V}$, $I_B = 0$) ($V_{CE} = 50 \text{ V}$, $I_B = 0$)	2N3771 2N3772	I_{CEO}	10 10	mA
Collector Cutoff Current ($V_{CE} = 50 \text{ V}$, $V_{BE(off)} = 1.5 \text{ V}$) ($V_{CE} = 100 \text{ V}$, $V_{BE(off)} = 1.5 \text{ V}$)	2N3771 2N3772	I_{CEV}	2.0 5.0	mA
Collector Cutoff Current ($V_{CE} = 50 \text{ V}$, $I_E = 0$) ($V_{CE} = 100 \text{ V}$, $I_E = 0$)	2N3771 2N3772	I_{CBO}	2.0 5.0	mA
Emitter Cutoff Current ($V_{EB} = 5.0 \text{ V}$, $I_c = 0$) ($V_{EB} = 7.0 \text{ V}$, $I_c = 0$)	2N3771 2N3772	I_{EBO}	5.0 5.0	mA

ON CHARACTERISTICS (1)


DC Current Gain ($I_c = 15 \text{ A}$, $V_{CE} = 4.0 \text{ V}$) ($I_c = 10 \text{ A}$, $V_{CE} = 4.0 \text{ V}$) ($I_c = 30 \text{ A}$, $V_{CE} = 4.0 \text{ V}$) ($I_c = 20 \text{ A}$, $V_{CE} = 4.0 \text{ V}$)	2N3771 2N3772 2N3771 2N3772	hFE	15 15 5.0 5.0	60 60
Collector - Emitter Saturation Voltage ($I_c = 15 \text{ A}$, $I_B = 1.5 \text{ A}$) ($I_c = 10 \text{ A}$, $I_B = 1.0 \text{ A}$) ($I_c = 30 \text{ A}$, $I_B = 6.0 \text{ A}$) ($I_c = 20 \text{ A}$, $I_B = 4.0 \text{ A}$)	2N3771 2N3772 2N3771 2N3772	$V_{CE(sat)}$		2.0 1.4 4.0 4.0
Base - Emitter On Voltage ($I_c = 15 \text{ A}$, $V_{CE} = 4.0 \text{ V}$) ($I_c = 10 \text{ A}$, $V_{CE} = 4.0 \text{ V}$)	2N3771 2N3772	$V_{BE(on)}$		2.7 2.2

DYNAMIC CHARACTERISTICS

Current Gain - Bandwidth Product (2) ($I_c = 1.0 \text{ A}$, $V_{CE} = 4.0 \text{ V}$, $f = 50 \text{ KHz}$)		f_T	0.2	MHz
---	--	-------	-----	-----

(1) Pulse Test: Pulse width = 300 us , Duty Cycle $\leq 2.0\%$ (2) $f_T = |h_{fe}| \cdot f_{test}$


ACTIVE-REGION SAFE OPERATING AREA (SOA)




There are two limitation on the power handling ability of a transistor: average junction temperature and second breakdown safe operating area curves indicate I_C - V_{CE} limits of the transistor that must be observed for reliable operation i.e., the transistor must not be subjected to greater dissipation than curves indicate.

The data of SOA curve is base on $T_{J(PK)}=200^\circ\text{C}$; T_C is variable depending on conditions. second breakdown pulse limits are valid for duty cycles to 10% provided $T_{J(PK)} \leq 200^\circ\text{C}$. At high case temperatures, thermal limitation will reduce the power that can be handled to values less than the limitations imposed by second breakdown.


DC CURRENT GAIN




COLLECTOR SATURATION REGION



TURN-OFF TIME



CAPACITANCES



Notice

MOSPEC reserves the rights to make changes of the content herein the document anytime without notification. MOSPEC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies. Please refer to MOSPEC website for the last document.

MOSPEC disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially incurred.

Application shown on the herein document are examples of standard use and operation. Customers are responsible for comprehending suitable use in particular applications. MOSPEC makes no representation or warranty that such application will be suitable for the specified use without further testing or modification.

The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by MOSPEC for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of MOSPEC or others.

These MOSPEC products are intended for usage in general electronic equipment. Please make sure to consult with MOSPEC before you use these MOSPEC products in equipment which require specialized quality and/or reliability, and in equipment which could have major impact to the welfare of human life (atomic energy control, aeronautics , traffic control, combustion control, safety devices etc.)