

COMPLEMENTARY SILICON TRANSISTORS

General Purpose use in power amplifier and switching circuits.

FEATURES:

- *DC Current Gain Specified
HFE=20 - 80 @ $I_c = 1.0 \text{ A}$
- * Low Collector-Emitter Saturation Voltage -
 $V_{CE(sat)} = 1.5 \text{ V (Max.) @ } I_c = 5.0 \text{ A}$


MAXIMUM RATINGS

Characteristic	Symbol	2N4901 2N5067	2N4902 2N5068	2N4903 2N5069	Unit
Collector-Emitter Voltage	V_{CBO}	40	60	80	V
Collector-Emitter Voltage	V_{CEO}	40	60	80	V
Emitter-Base Voltage	V_{EB}	5.0			V
Collector Current-Continuous -Peak	I_c	5.0 10			A
Base current - Continuous	I_B	1.0			A
Total Power Dissipation @ $T_c = 25^\circ\text{C}$ Derate above 25°C	P_D	87.5 0.5			W W/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	T_J, T_{STG}	- 65 to +200			$^\circ\text{C}$

THERMAL CHARACTERISTICS


Characteristic	Symbol	Max	Unit
Thermal Resistance Junction to Case	$R_{\theta jc}$	2.0	$^\circ\text{C/W}$

FIGURE -1 POWER DERATING




PNP	NPN
2N4901	2N5067
2N4902	2N5068
2N4903	2N5069

5.0 AMPERE
COMPLEMENTARY SILICON
POWER TRANSISTORS
40-80 Volts
87.5 Watts



TO-3



PIN 1.BASE
2.EMITTER
COLLECTOR(CASE)

DIM	MILLIMETERS	
	MIN	MAX
A	38.75	39.96
B	19.28	22.23
C	7.96	9.28
D	11.18	12.19
E	25.20	26.67
F	0.92	1.09
G	1.38	1.62
H	29.90	30.40
I	16.64	17.30
J	3.88	4.36
K	10.67	11.18

2N4901, 4902, 4903 PNP / 2N5067, 2N5068, 2N5069 NPN

ELECTRICAL CHARACTERISTICS ($T_c = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

OFF CHARACTERISTICS

Collector - Emitter Sustaining Voltage (1) ($I_C = 200\text{ mA}$, $I_B = 0$) 2N4901, 2N5067 2N4902, 2N5068 2N4903, 2N5069	$V_{CE(sus)}$	40 60 80		V
Collector Cutoff Current ($V_{CE} = \text{Rated } V_{CEO}$, $I_B = 0$)	I_{CEO}		1.0	mA
Collector Cutoff Current ($V_{CE} = \text{Rated } V_{CEO}$, $V_{BE(off)} = 1.5\text{ V}$) ($V_{CE} = \text{Rated } V_{CEO}$, $V_{BE(off)} = 1.5\text{ V}$, $T_c = 150^\circ\text{C}$)	I_{CEX}		0.1 2.0	mA
Collector Cutoff Current ($V_{CB} = \text{Rated } V_{CBO}$, $I_E = 0$)	I_{CBO}		0.1	mA
Emitter Cutoff Current ($V_{EB} = 5.0\text{ V}$, $I_C = 0$)	I_{EBO}		1.0	mA

ON CHARACTERISTICS (1)

DC Current Gain ($I_C = 1.0\text{ A}$, $V_{CE} = 2.0\text{ V}$) ($I_C = 5.0\text{ A}$, $V_{CE} = 2.0\text{ V}$)	h_{FE}	20 7.0	80	
Collector-Emitter Saturation Voltage ($I_C = 1.0\text{ A}$, $I_B = 0.1\text{ A}$) ($I_C = 5.0\text{ A}$, $I_B = 1.0\text{ A}$)	$V_{CE(sat)}$		0.4 1.5	V
Base-Emitter On Voltage ($I_C = 1.0\text{ A}$, $V_{CE} = 2.0\text{ V}$)	$V_{BE(on)}$		1.2	V


DYNAMIC CHARACTERISTICS

Current - Gain - Bandwidth Product (2) ($I_C = 1.0\text{ A}$, $V_{CE} = 10\text{ V}$, $f = 1.0\text{ MHz}$)	f_T	4.0		MHz
Small-Signal Current Gain ($I_C = 0.5\text{ A}$, $V_{CE} = 10\text{ V}$, $f = 1.0\text{ KHz}$)	h_{fe}	20		

(1) Pulse Test: Pulse width = 300 μs , Duty Cycle $\leq 2.0\%$

(2) $f_T = |h_{fe}| \cdot f_{test}$


ACTIVE-REGION SAFE OPERATING AREA (SOA)




There are two limitation on the power handling ability of a transistor: average junction temperature and second breakdown safe operating area curves indicate I_c - V_{ce} limits of the transistor that must be observed for reliable operation i.e., the transistor must not be subjected to greater dissipation than curves indicate.

The data of SOA curve is base on $T_{J(PK)}=200^\circ\text{C}$; T_c is variable depending on conditions. second breakdown pulse limits are valid for duty cycles to 10% provided $T_{J(PK)} \leq 200^\circ\text{C}$. At high case temperatures, thermal limitation will reduce the power that can be handled to values less than the limitations imposed by second breakdown.


CAPACITANCES




COLLECTOR CUT-OFF REGION




TURN-ON TIME




TURN-OFF TIME




COLLECTOR SATURATION REGION



DC CURRENT GAIN



"ON" VOLTAGE



Notice

MOSPEC reserves the rights to make changes of the content herein the document anytime without notification. MOSPEC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies. Please refer to MOSPEC website for the last document.

MOSPEC disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially incurred.

Application shown on the herein document are examples of standard use and operation. Customers are responsible for comprehending suitable use in particular applications. MOSPEC makes no representation or warranty that such application will be suitable for the specified use without further testing or modification.

The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by MOSPEC for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of MOSPEC or others.

These MOSPEC products are intended for usage in general electronic equipment. Please make sure to consult with MOSPEC before you use these MOSPEC products in equipment which require specialized quality and/or reliability, and in equipment which could have major impact to the welfare of human life (atomic energy control, aeronautics , traffic control, combustion control, safety devices etc.)