

DARLINGTON COMPLEMENTARY SILICON POWER TRANSISTORS

General-purpose power amplifier and low frequency switching applications

FEATURES:

- * Low Collector-Emitter Saturation Voltage -

$$V_{CE(SAT)} = 2.0V(\text{Max.}) @ I_C = 4.0A$$

$$= 3.0V(\text{Max.}) @ I_C = 8.0A$$

- * Monolithic Construction With Built-In Base-Emitter Shunt Resistors


MAXIMUM RATINGS

Characteristic	Symbol	2N6053 2N6055	2N6054 2N6056	Unit
Collector-Emitter Voltage	V_{CEO}	60	80	V
Collector-Base Voltage	V_{CBO}	60	80	V
Emitter-Base Voltage	V_{EBO}	5.0		V
Collector Current-Continuous -Peak	I_C I_{CM}	8.0 16		A
Base Current	I_B	120		mA
Total Power Dissipation @ $T_C = 25^\circ\text{C}$ Derate above 25°C	P_D	100 0.571		W W/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	T_J, T_{STG}	- 65 to +200		$^\circ\text{C}$

THERMAL CHARACTERISTICS


Characteristic	Symbol	Max	Unit
Thermal Resistance Junction to Case	$R_{\theta jc}$	1.75	$^\circ\text{C/W}$

FIGURE -1 POWER DERATING




PNP	NPN
2N6053	2N6055
2N6054	2N6056

DARLINGTON
8 AMPERE
COMPLEMENTARY SILICON
POWER TRANSISTORS
60 - 80 Volts
100 Watts



TO-3



PIN 1. BASE
2. EMITTER
COLLECTOR (CASE)

DIM	MILLIMETERS	
	MIN	MAX
A	38.75	39.96
B	19.28	22.23
C	7.96	9.28
D	11.18	12.19
E	25.20	26.67
F	0.92	1.09
G	1.38	1.62
H	29.90	30.40
I	16.64	17.30
J	3.88	4.36
K	10.67	11.18

ELECTRICAL CHARACTERISTICS ($T_c = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

OFF CHARACTERISTICS

Collector - Emitter Sustaining Voltage (1) ($I_C = 100\text{ mA}$, $I_B = 0$) 2N6053, 2N6055 2N6054, 2N6056	$V_{CE(sus)}$	60 80		V
Collector Cutoff Current ($V_{CE} = 30\text{ V}$, $I_B = 0$) ($V_{CE} = 40\text{ V}$, $I_B = 0$) 2N6053, 2N6055 2N6054, 2N6056	I_{CEO}		0.5 0.5	mA
Collector Cutoff Current ($V_{CE} = 60\text{ V}$, $V_{BE(off)} = 1.5\text{ V}$) ($V_{CE} = 80\text{ V}$, $V_{BE(off)} = 1.5\text{ V}$) ($V_{CE} = 60\text{ V}$, $V_{BE(off)} = 1.5\text{ V}$, $T_c = 150^\circ\text{C}$) ($V_{CE} = 80\text{ V}$, $V_{BE(off)} = 1.5\text{ V}$, $T_c = 150^\circ\text{C}$) 2N6053, 2N6055 2N6054, 2N6056 2N6053, 2N6055 2N6054, 2N6056	I_{CEX}		0.5 0.5 5.0 5.0	mA
Emitter Cutoff Current ($V_{EB} = 5.0\text{ V}$, $I_C = 0$)	I_{EBO}		2.0	mA

ON CHARACTERISTICS (1)

DC Current Gain ($I_C = 4.0\text{ A}$, $V_{CE} = 3.0\text{ V}$) ($I_C = 8.0\text{ A}$, $V_{CE} = 3.0\text{ V}$)	h_{FE}	750 100	18000	
Collector-Emitter Saturation Voltage ($I_C = 4.0\text{ A}$, $I_B = 16\text{ mA}$) ($I_C = 8.0\text{ A}$, $I_B = 80\text{ mA}$)	$V_{CE(sat)}$		2.0 3.0	V
Base-Emitter On Voltage ($I_C = 4\text{ A}$, $V_{CE} = 3.0\text{ V}$)	$V_{BE(on)}$		2.8	V
Base-Emitter Saturation Voltage ($I_C = 8.0\text{ A}$, $I_B = 80\text{ mA}$)	$V_{BE(sat)}$		4.0	V


DYNAMIC CHARACTERISTICS

Output capacitance ($V_{CB} = 10\text{ V}$, $I_E = 0$, $f = 0.1\text{ MHz}$) 2N6053, 2N6054 2N6055, 2N6056	C_{ob}		350 220	pF
Small-Signal Current Gain ($I_C = 3.0\text{ A}$, $V_{CE} = 3.0\text{ V}$, $f = 1.0\text{ KHz}$)	h_{fe}	300		


(1) Pulse Test: Pulse width $\leq 300\text{ }\mu\text{s}$, Duty Cycle $\leq 2.0\%$

PNP 2N6053, 2N6054


DC CURRENT GAIN



COLLECTOR SATURATION REGION




"ON" VOLTAGES




NPN 2N6055, 2N6056


DC CURRENT GAIN




COLLECTOR SATURATION REGION




"ON" VOLTAGES




SWITCHING TIME



CAPACITANCES



ACTIVE-REGION SAFE OPERATING AREA (SOA)



There are two limitation on the power handling ability of a transistor: average junction temperature and second breakdown safe operating area curves indicate I_c - V_{CE} limits of the transistor that must be observed for reliable operation i.e., the transistor must not be subjected to greater dissipation than curves indicate.

The data of SOA curve is base on $T_{J(PK)}=200^\circ C$; T_C is variable depending on conditions. second breakdown pulse limits are valid for duty cycles to 10% provided $T_{J(PK)} \leq 200^\circ C$. At high case temperatures, thermal limitation will reduce the power that can be handled to values less than the limitations imposed by second breakdown.

Notice

MOSPEC reserves the rights to make changes of the content herein the document anytime without notification. MOSPEC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies. Please refer to MOSPEC website for the last document.

MOSPEC disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially incurred.

Application shown on the herein document are examples of standard use and operation. Customers are responsible for comprehending suitable use in particular applications. MOSPEC makes no representation or warranty that such application will be suitable for the specified use without further testing or modification.

The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by MOSPEC for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of MOSPEC or others.

These MOSPEC products are intended for usage in general electronic equipment. Please make sure to consult with MOSPEC before you use these MOSPEC products in equipment which require specialized quality and/or reliability, and in equipment which could have major impact to the welfare of human life (atomic energy control, aeronautics , traffic control, combustion control, safety devices etc.)