

NPN SILICON POWER TRANSISTORS

...designed for use in B/W TV horizontal output applications.

FEATURES:


- * Collector-Emitter Sustaining Voltage-
 $V_{CE(sus)} = 70 \text{ V (Min)-2SC681}$
 $= 80 \text{ V (Min)-2SC681ARD}$
 $= 80 \text{ V (Min)-2SC681AYL}$
- * Low Collector-Emitter Saturation Voltage
 $V_{CE(sat)} = 2.0 \text{ V (Max) @ } I_C = 5.0 \text{ A, } I_B = 0.6 \text{ A}$

MAXIMUM RATINGS

Characteristic	Symbol	2SC			Unit
		681	681ARD	681AYL	
Collector-Emitter Voltage	V_{CEO}	70	80	80	V
Collector-Base Voltage	V_{CBO}	200	250	300	V
Emitter-Base Voltage	V_{EBO}	5.0			V
Collector Current-Continuous -Peak	I_C	6.0	6.0	6.0	A
	I_{CM}	20	20	25	
Base Current	I_B	2.0			A
Total Power Dissipation @ $T_C = 25^\circ\text{C}$ Derate above 25°C	P_D	50			W
		0.4			W/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	T_J, T_{STG}	- 65 to +150			$^\circ\text{C}$


THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance Junction to Case	$R_{\theta jc}$	2.5	$^\circ\text{C/W}$




NPN
2SC681
2SC681ARD
2SC681AYL

6 AMPERE
SILICON POWER
TRANSISTOR
70-80 VOLTS
50 WATTS



TO-3



PIN 1.BASE
 2.EMITTER
 COLLECTOR(CASE)

DIM	MILLIMETERS	
	MIN	MAX
A	38.75	39.96
B	19.28	22.23
C	7.96	9.28
D	11.18	12.19
E	25.20	26.67
F	0.92	1.09
G	1.38	1.62
H	29.90	30.40
I	16.64	17.30
J	3.88	4.36
K	10.67	11.18

ELECTRICAL CHARACTERISTICS ($T_c = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

OFF CHARACTERISTICS

Collector - Emitter Sustaining Voltage (1) ($I_c = 50\text{ mA}$, $I_B = 0$)	2SC681 2SC681ARD 2SC681AYL	$V_{CEO(sus)}$	70 80 80	V
Collector Cutoff Current ($V_{CE} = 200\text{ V}$, $I_E = 0$) ($V_{CE} = 250\text{ V}$, $I_E = 0$) ($V_{CE} = 300\text{ V}$, $I_E = 0$)	2SC681 2SC681ARD 2SC681AYL	I_{CBO}	1.0 1.0 1.0	mA
Emitter Cutoff Current ($V_{EB} = 5.0\text{ V}$, $I_C = 0$)		I_{EBO}	10	mA

ON CHARACTERISTICS (1)


Collector-Emitter Saturation Voltage ($I_c = 5.0\text{ A}$, $I_B = 0.6\text{ A}$)	$V_{CE(sat)}$	2.0	V
Base-Emitter Saturation Voltage ($I_c = 5.0\text{ A}$, $I_B = 0.6\text{ A}$)	$V_{BE(sat)}$	1.5	V

SWITCHING CHARACTERISTICS


Fall Time ($I_c = 5.0\text{ A}$, $I_{B1} = 0.6\text{ A}$, $I_{B2} = -1.0\text{ A}$, $V_{CC} = 25\text{ V}$)	t_f	0.5	us
---	-------	-----	----

(1) Pulse Test: Pulse width = 300 us , Duty Cycle $\leq 2.0\%$


REVERSE BIASE SAFE OPERATING AREA




$I_C - V_{BE}$




$I_C - V_{CE}$




$I_C - V_{CE}$



COLLECTOR SATURATION REGION



$I_B - V_{BE}$



Notice

MOSPEC reserves the rights to make changes of the content herein the document anytime without notification. MOSPEC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies. Please refer to MOSPEC website for the last document.

MOSPEC disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially incurred.

Application shown on the herein document are examples of standard use and operation. Customers are responsible for comprehending suitable use in particular applications. MOSPEC makes no representation or warranty that such application will be suitable for the specified use without further testing or modification.

The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by MOSPEC for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of MOSPEC or others.

These MOSPEC products are intended for usage in general electronic equipment. Please make sure to consult with MOSPEC before you use these MOSPEC products in equipment which require specialized quality and/or reliability, and in equipment which could have major impact to the welfare of human life (atomic energy control, aeronautics , traffic control, combustion control, safety devices etc.)