

HORIZONTAL DEFLECTION TRANSISTOR

...specifically designed for use in large screen color deflection circuits.

FEATURES:

- * Collector-Emitter Sustaining Voltage -
 $V_{CEX} = 1300 \text{ V (Min.) - BU204}$
 $= 1500 \text{ V (Min.) - BU205}$
- * Glassivated Base-Collector Junction


MAXIMUM RATINGS

Characteristic	Symbol	BU204	BU205	Unit
Collector-Emitter Voltage	V_{CEO}	600	700	V
Collector-Emitter Voltage	V_{CEX}	1300	1500	V
Emitter-Base Voltage	V_{EBO}	5.0		V
Collector Current - Continuous - Peak	I_C	2.5 3.0		A
Base Current - Continuous	I_B	1.0		A
Total Power Dissipation @ $T_C = 25^\circ\text{C}$ Derate above 25°C	P_D	36 0.4		W W/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	T_J, T_{STG}	- 65 to +115		$^\circ\text{C}$

THERMAL CHARACTERISTICS


Characteristic	Symbol	Max	Unit
Thermal Resistance Junction to Case	$R_{\theta jc}$	2.5	$^\circ\text{C/W}$

FIGURE -1 POWER DERATING




NPN
BU204
BU205

2.5 AMPERE
POWER
TRANSISTORS
1300-1500 VOLTS
36 WATTS



TO-3



PIN 1.BASE
 2.EMITTER
 COLLECTOR(CASE)

DIM	MILLIMETERS	
	MIN	MAX
A	38.75	39.96
B	19.28	22.23
C	7.96	9.28
D	11.18	12.19
E	25.20	26.67
F	0.92	1.09
G	1.38	1.62
H	29.90	30.40
I	16.64	17.30
J	3.88	4.36
K	10.67	11.18

ELECTRICAL CHARACTERISTICS ($T_c = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

OFF CHARACTERISTICS

Collector - Emitter Sustaining Voltage (1) ($I_C = 100\text{ mA}$, $I_B = 0$)	BU204 BU205	$V_{CE(sus)}$	600 700	V
Collector Cutoff Current ($V_{CE} = 1300\text{ V}$, $V_{BE} = 0$) ($V_{CE} = 1500\text{ V}$, $V_{BE} = 0$)	BU204 BU205	I_{CES}	1.0 1.0	mA
Emitter Cutoff Current ($V_{EB} = 5.0\text{ V}$, $I_C = 0$)		I_{EBO}	10	mA

ON CHARACTERISTICS (1)

DC Current Gain ($I_C = 2.0\text{ A}$, $V_{CE} = 5.0\text{ V}$)	h_{FE}	2.0		
Collector - Emitter Saturation Voltage ($I_C = 2.0\text{ A}$, $I_B = 1.0\text{ A}$)	$V_{CE(sat)}$		5.0	V
Base - Emitter Saturation Voltage ($I_C = 2.0\text{ A}$, $I_B = 1.0\text{ A}$)	$V_{BE(sat)}$		1.5	V

DYNAMIC CHARACTERISTICS


Current Gain - Bandwidth Product ($I_C = 0.1\text{ A}$, $V_{CE} = 5.0\text{ V}$, $f = 1.0\text{ MHz}$)	f_T	4.0(typ)		MHz
Output Capacitance ($V_{CE} = 10\text{ V}$, $I_E = 0$, $f = 1.0\text{ MHz}$)	C_{ob}	50(typ)		pF

SWITCHING CHARACTERISTICS


Fall Time ($I_C = 2.0\text{ A}$, $I_{B1} = 1.0\text{ A}$, $L_B = 25\text{ uH}$)	t_f	0.65(typ)		us
--	-------	-----------	--	----

(1) Pulse Test: Pulse width $\leq 300\text{ us}$, Duty Cycle $\leq 2.0\%$


COLLECTOR SATURATION REGION




DC CURRENT GAIN




"ON" VOLTAGES



SWITCHING BEHAVIOR VERSUS I_{CM}



FORWARD BIAS SAFE OPERATING AREA



Notice

MOSPEC reserves the rights to make changes of the content herein the document anytime without notification. MOSPEC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies. Please refer to MOSPEC website for the last document.

MOSPEC disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially incurred.

Application shown on the herein document are examples of standard use and operation. Customers are responsible for comprehending suitable use in particular applications. MOSPEC makes no representation or warranty that such application will be suitable for the specified use without further testing or modification.

The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by MOSPEC for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of MOSPEC or others.

These MOSPEC products are intended for usage in general electronic equipment. Please make sure to consult with MOSPEC before you use these MOSPEC products in equipment which require specialized quality and/or reliability, and in equipment which could have major impact to the welfare of human life (atomic energy control, aeronautics , traffic control, combustion control, safety devices etc.)