## 700V Super-junction Power MOSFET

DESCRIPTION：

·Very low FOM $R_{DS(on)}$×Qg

·Ultra fast body diode

·100% avalanche tested

·Easy to use/drive

·RoHS compliant

| | |
|---|---|
| $V_{DSS}$ | 700V |
| $I_D$ | 7A |
| $R_{DS(ON)_Typ.}$ @$V_{GS}$=10V | 0.53Ω |




TO-251

TYPICAL APPLICATIONS：

·Switch Mode Power Supply (SMPS)

·Uninterruptible Power Supply (UPS)

·Power Factor Correction (PFC)

·Charger

MAXIMUM RATINGS (at $T_C$ = 25 °C, unless otherwise specified)

| Characteristic | Condition | Symbol | Value | Unit |
|---|---|---|---|---|
| Continuous Drain Current | Tc=25℃<br>Tc=100℃ | $I_D$ | 7<br>4.2 | A |
| Pulsed Drain Current (1) | | $I_{D\ pulse}$ | 21 | A |
| Gate-Source Voltage | | $V_{GS}$ | ±30 | V |
| Single Pulsed Avalanche Energy (2) | | $E_{AS}$ | 142 | mJ |
| Repetitive Avalanche Energy (2) | | $E_{AR}$ | 0.21 | mJ |
| Avalanche Current | | $I_{AR}$ | 1.3 | A |
| Power dissipation | | $P_D$ | 63 | W |
| Continuous Diode Forward Current | | $I_S$ | 6 | A |
| Diode Pulsed Current (1) | | $I_{S\ pulse}$ | 21 | A |
| Reverse Diode dv/dt | | dv/dt | 15 | V/ns |
| Junction & Storage temperature Range | | $T_J$, $T_{STG}$ | -55~+150 | ℃ |

Notes： 1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature.

2. $I_{AS}$ = 2.4A, $V_{DD}$ = 50V, $R_G$ = 25Ω, Starting $T_J$ = 25°C

ELECTRICAL CHARATERISTICS (at $T_J$ = 25 °C, unless otherwise specified)

| Characteristic | Symbol | Min. | Typ. | Max. | Unit |
|---|---|---|---|---|---|
| Drain-Source Breakdown Voltage<br>VGS = 0V, ID = 250uA | $V_{(BR)DSS}$ | 700 | | | V |
| Zero Gate Voltage Drain Current<br>VDS = 700 V, VGS = 0 V ,Tj=25℃<br>VDS = 700 V, VGS = 0 V ,Tj=150℃ | $I_{DSS}$ | | | 1<br>100 | uA |
| Gate-Source Leakage Current<br>VGS = ±30V, VDS = 0V | $I_{GSS}$ | | | ±100 | nA |
| Gate-Source threshold voltage<br>VDS = VGS, ID = 250uA | $V_{GS(th)}$ | 2.5 | | 4.5 | V |
| Drain-Source On-State Resistance<br>VGS = 10V, ID = 3.5A | $R_{DS(on)}$ | | 0.53 | 0.6 | Ω |
| Gate Resistance<br>f=1MHz | Rg | | 7 | | Ω |
| Input capacitance<br>f=1MHz, VDS=100 V, VGS=0 V | $C_{iss}$ | | 509 | | pF |
| Output capacitance<br>f=1MHz, VDS=100 V, VGS=0 V | $C_{oss}$ | | 23 | | pF |
| Reverse transfer capacitance<br>f=1MHz, VDS=100 V, VGS=0 V | $C_{rss}$ | | 1.5 | | pF |
| Total Gate Charge<br>VDS= 520V, ID= 7A,VGS= 10V | $Q_G$ | | 13 | | nC |
| Gate to Source Charge<br>VDS= 520V, ID= 7A,VGS= 10V | $Q_{GS}$ | | 2.8 | | nC |
| Gate to Drain Charge<br>VDS= 520V, ID= 7A,VGS= 10V | $Q_{GD}$ | | 5.6 | | nC |
| Turn-on delay time<br>VDD=400 V, ID=7A, $R_{GEN}$=25Ω | td (ON) | | 55 | | ns |
| Rise time<br>VDD=400 V, ID=7A, $R_{GEN}$=25Ω | tr | | 61 | | ns |
| Turn-off delay time<br>VDD=400 V, ID=7A, $R_{GEN}$=25Ω | td (OFF) | | 117 | | ns |
| Fall time<br>VDD=400 V, ID=7A, $R_{GEN}$=25Ω | tf | | 42 | | ns |
| Diode Forward Voltage<br>VGS = 0V, $I_{SD}$ =3.5A | $V_{SD}$ | | 0.9 | 1.2 | V |
| Revers Recovery Time<br>$V_R$=400V, $I_F$ =7A, $di_F/dt$ = 100A/us | Trr | | 321 | | ns |
| Revers Recovery Charge<br>$V_R$=400V, $I_F$ =7A, $di_F/dt$ = 100A/us | Qrr | | 3.4 | | uC |
| Peak Reverse Recovery Current<br>$V_R$=400V, $I_F$ =7A, $di_F/dt$ = 100A/us | Irrm | | 21.2 | | A |

THERMAL CHARACTERISTICS

| Characteristic | Condition | Symbol | Value | Unit |
|---|---|---|---|---|
| Thermal resistance, | Junction to Ambient<br>Junction to Case | $R_{\theta JA}$<br>$R_{\theta JC}$ | 62<br>2.0 | ℃/W |

Typical Performance Characteristics





Figure 1. Output Characteristics





Figure 2. Transfer Characteristics





Figure 3. On-Resistance vs. Drain Current





Figure 4. Capacitance





Figure 5. Gate Charge





Figure 6. Body Diode Forward Voltage





Figure 7. On-Resistance vs.Temperature





Figure8. Breakdown voltage vs. Junction Temperature





Figure 9. Transient Thermal Impedance





Figure 10. Safe Operation Area







Figure 11. Typ. Coss Stored Energy

·Circuit diagram




·Package outlines : Dimensions in (mm)



# Notice

MOSPEC reserves the rights to make changes of the content herein the document anytime without notification. MOSPEC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies. Please refer to MOSPEC website for the last document.

MOSPEC disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially incurred.

Application shown on the herein document are examples of standard use and operation. Customers are responsible for comprehending suitable use in particular applications. MOSPEC makes no representation or warranty that such application will be suitable for the specified use without further testing or modification.

The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by MOSPEC for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of MOSPEC or others.

These MOSPEC products are intended for usage in general electronic equipment. Please make sure to consult with MOSPEC before you use these MOSPEC products in equipment which require specialized quality and/or reliability, and in equipment which could have major impact to the welfare of human life ( atomic energy control, aeronautics , traffic control, combustion control, safety devices etc.)