60V N-Channel Power MOSFET

V_{DSS}	60V
I_D @V_{GS}=10V	0.4A
$R_{DS(ON)_Typ.}$ @V_{GS}=10V	1788mΩ

DESCRIPTION：

·Excellent $R_{DS(ON)}$, and Low Gate Charge.


·Halogen-free; RoHS-compliant

·100% UIS Tested

·100% ΔVds Tested

·Pb-free plating

·ESD Protected, HBM>2KV



SOT-23

TYPICAL APPLICATIONS：

·Load Switch

·PWM Application

·Power Management

MAXIMUM RATINGS (at T_C = 25 °C, unless otherwise specified)

Characteristic	Condition	Symbol	Value	Unit
Drain-Source Voltage		V_{DS}	60	V
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current	Tc=25℃ Tc=100℃	I_D	0.4 0.2	A
Pulsed Drain Current		I_{DM}	Refer to Fig.4	A
Power dissipation	Tc=25℃ Tc=100℃	P_D	0.7 0.3	W
Junction & Storage temperature Range		T_J, T_{STG}	-55~+150	℃

THERMAL CHARACTERISTICS

Characteristic	Condition	Symbol	Value	Unit
Thermal resistance,	Junction to Ambient	$R_{\theta JA}$	176	℃/W

ELECTRICAL CHARATERISTICS (at T_J = 25 °C, unless otherwise specified)

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage VGS = 0V, ID = 250uA	$V_{(BR)DSS}$	60			V
Zero Gate Voltage Drain Current VDS = 60 V, VGS = 0 V	I_{DSS}			1.0	uA
Gate-Source Leakage Current VGS = ±20V, VDS = 0V	I_{GSS}			±10	nA
Gate-Source threshold voltage VDS = VGS, ID = 250uA	$V_{GS(th)}$	1.1	1.5	2.0	V
Drain-Source On-State Resistance VGS = 10V, ID = 0.3A VGS = 4.5V, ID = 0.2A	$R_{DS(on)}$		1788 1968	2200 2870	mΩ
Input capacitance f=1MHz, VDS=30 V, VGS=0 V	C_{iss}		18.5		pF
Output capacitance f=1MHz, VDS=30 V, VGS=0 V	C_{oss}		4.6		pF
Reverse transfer capacitance f=1MHz, VDS=30 V, VGS=0 V	C_{rss}		1.5		pF
Gate Resistance VGS = 0V, VDS= 0V, f = 1MHz	R_G		12		Ω
Total Gate Charge VDS= 10V, ID= 1A, VGS= 0 to 4.5V	Q_G		0.5		nC
Gate to Source Charge VDS= 10V, ID= 1A, VGS= 0 to 4.5V	Q_{GS}		0.4		nC
Gate to Drain Charge VDS= 10V, ID= 1A, VGS= 0 to 4.5V	Q_{GD}		0.1		nC
Turn-on delay time VDS= 15V, VGS= 10V, ID= 0.2A, R_{GEN}=3Ω	$td_{(ON)}$		0.6		ns
Rise time VDS= 15V, VGS= 10V, ID= 0.2A, R_{GEN}=3Ω	tr		1.9		ns
Turn-off delay time VDS= 15V, VGS= 10V, ID= 0.2A, R_{GEN}=3Ω	$td_{(OFF)}$		3.8		ns
Fall time VDS= 15V, VGS= 10V, ID= 0.2A, R_{GEN}=3Ω	tf		3.3		ns
Revers Recovery Time IF=0.5A, di/dt = 100A/us	Trr		18		ns
Revers Recovery Charge IF=0.5A, di/dt = 100A/us	Qrr		3.5		nC
Maximum Pulsed Body Diode Forward Current	IS			0.4	A
Maximum Pulsed Body Diode Forward Current	ISM			1.5	A
Diode Forward Voltage VGS = 0V, I_S = 0.3A	V_{SD}			1.2	V

Typical Performance Characteristics




Figure 1. Power De-rating




Figure 2. Current De-rating




Figure 3. Normalized Maximum Transient Thermal Impedance




Figure 4. Peak Current Capacity




Figure 5. Output Characteristics




Figure 6. Typical Transfer Characteristics




Figure 7. On-resistance vs. Drain Current




Figure8. Body Diode Characteristics




Figure 9. Gate Charge Characteristics




Figure 10. Capacitance Characteristics




Figure11. Normalized Breakdown voltage vs. Junction Temperature




Figure 12. Normalized on Resistance vs. Junction Temperature




Figure 13. Normalized Threshold Voltage vs. Junction Temperature




Figure14. $R_{DS(ON)}$ vs. V_{GS}






Figure 15. Maximum Safe Operating Area

·Circuit diagram



·Package outlines : Dimensions in (mm)



COMMON DIMENSIONS
(UNITS OF MEASURE=mm)

SYMBOL	MIN	NOM	MAX
A	0.90	1.05	1.20
A1	0.00	0.05	0.10
A2	0.90	1.00	1.10
b	0.30	0.40	0.50
c	0.08	0.10	0.15
D	2.80	2.90	3.00
E	1.20	1.30	1.40
E1	2.30	2.40	2.50
L	0.30	0.40	0.50
θ	0°	5°	10°
L1	0.55 REF		
e	0.95 BSC		
e1	1.90 REF		

Notice

MOSPEC reserves the rights to make changes of the content herein the document anytime without notification. MOSPEC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies. Please refer to MOSPEC website for the last document.

MOSPEC disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially incurred.

Application shown on the herein document are examples of standard use and operation. Customers are responsible for comprehending suitable use in particular applications. MOSPEC makes no representation or warranty that such application will be suitable for the specified use without further testing or modification.

The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by MOSPEC for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of MOSPEC or others.

These MOSPEC products are intended for usage in general electronic equipment. Please make sure to consult with MOSPEC before you use these MOSPEC products in equipment which require specialized quality and/or reliability, and in equipment which could have major impact to the welfare of human life (atomic energy control, aeronautics , traffic control, combustion control, safety devices etc.)