
650V Super-junction Power MOSFET

DESCRIPTION：
- Very low FOM $R_{DS(on)}$×Qg
- Ultra fast body diode
- 100% avalanche tested
- Easy to use/drive
- RoHS compliant

V_{DSS}	650V
I_D	110A
$R_{DS(ON)_Typ.}$ @V_{GS}=10V	19.5mΩ

TYPICAL APPLICATIONS：
- Switch Mode Power Supply (SMPS)
- Uninterruptible Power Supply (UPS)
- Power Factor Correction (PFC)
- LLC Half bridge
- Charger



TO-247

MAXIMUM RATINGS (at T_C = 25 °C, unless otherwise specified)

Characteristic	Condition	Symbol	Value	Unit
Continuous Drain Current	Tc=25℃ Tc=100℃	I_D	110 70	A
Pulsed Drain Current (1)		$I_{D\ pulse}$	330	A
Gate-Source Voltage		V_{GS}	±30	V
Single Pulsed Avalanche Energy (2)		E_{AS}	793	mJ
Repetitive Avalanche Energy (2)		E_{AR}	3.17	mJ
Avalanche Current		I_{AS}	12.6	A
Power dissipation		P_D	595	W
Continuous Diode Forward Current		I_S	110	A
Diode Pulsed Current (1)		$I_{S\ pulse}$	330	A
Reverse Diode dv/dt		dv/dt	50	V/ns
Junction & Storage temperature Range		T_J, T_{STG}	-55~+150	℃

Notes： 1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature.
2. L = 10mH, V_{DD} = 50V, R_G = 25Ω, Starting T_J = 25°C

ELECTRICAL CHARATERISTICS (at T_J = 25 °C, unless otherwise specified)

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage VGS = 0V, ID = 250uA	$V_{(BR)DSS}$	650			V
Zero Gate Voltage Drain Current VDS = 650 V, VGS = 0 V ,Tj=25℃ VDS = 650 V, VGS = 0 V ,Tj=150℃	I_{DSS}			10 500	uA
Gate-Source Leakage Current VGS = ±30V, VDS = 0V	I_{GSS}			±100	nA
Gate-Source threshold voltage VDS = VGS, ID = 250uA	$V_{GS(th)}$	3.0	3.7	5.0	V
Drain-Source On-State Resistance VGS = 10V, ID = 50A	$R_{DS(on)}$		19.5	22	mΩ
Gate Resistance f=1MHz	Rg		0.89		Ω
Input capacitance f=1MHz, VDS=50 V, VGS=0 V	C_{iss}		10687		pF
Output capacitance f=1MHz, VDS=50 V, VGS=0 V	C_{oss}		437		pF
Reverse transfer capacitance f=1MHz, VDS=50 V, VGS=0 V	C_{rss}		63		pF
Total Gate Charge VDS= 520V, ID= 50A,VGS= 10V	Q_G		185		nC
Gate to Source Charge VDS= 520V, ID= 50A,VGS= 10V	Q_{GS}		59.5		nC
Gate to Drain Charge VDS= 520V, ID= 50A,VGS= 10V	Q_{GD}		56		nC
Turn-on delay time VDD=400 V, ID=50A, R_{GEN}=2Ω	td (ON)		483		ns
Rise time VDD=400 V, ID=50A, R_{GEN}=2Ω	tr		7.36		ns
Turn-off delay time VDD=400 V, ID=50A, R_{GEN}=2Ω	td (OFF)		191		ns
Fall time VDD=400 V, ID=50A, R_{GEN}=2Ω	tf		15.3		ns
Diode Forward Voltage VGS = 0V, I_{SD} =50A	V_{SD}		0.9	1.2	V
Revers Recovery Time V_R=400V, I_S =50A, di_F/dt = 100A/us	Trr		291		ns
Revers Recovery Charge V_R=400V, I_S =50A, di_F/dt = 100A/us	Qrr		1.552		uC
Peak Reverse Recovery Current V_R=400V, I_S =50A, di_F/dt = 100A/us	Irrm		10		A

THERMAL CHARACTERISTICS

Characteristic	Condition	Symbol	Value	Unit
Thermal resistance,	Junction to Ambient Junction to Case	$R_{\theta JA}$ $R_{\theta JC}$	62 0.21	℃/W

Typical Performance Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current




Figure 4. Capacitance




Figure 5. Gate Charge




Figure 6. Body Diode Forward Voltage




Figure 7. On-Resistance vs.Temperature




Figure8. Breakdown voltage vs. Junction Temperature




Figure 9. Transient Thermal Impedance






Figure 10. Safe Operation Area

• Circuit diagram



• Package outlines : Dimensions in (mm)



SYMBOL	MIN	NOM	MAX
A	4.90	5.00	5.10
A1	1.90	2.00	2.10
b	1.15	1.20	1.25
b1	2.95	3.00	3.05
b2	1.95	2.00	2.05
B1	3.00	3.10	3.20
B2	1.90	2.00	2.10
c	0.55	0.60	0.65
D	20.90	21.00	21.10
D1	16.45	16.55	16.65
D2	1.07	1.17	1.27
D3	8.15	8.20	8.25
E	15.70	15.80	15.90
E1	13.16	13.26	13.36
E2	2.40	2.50	2.60
E3	6.10	6.20	6.30
E4	12.70	12.80	12.90
F	0.75	0.85	0.95
F1	5.70	5.80	5.90
F2	4.90	5.00	5.10
F3	9.90	10.00	10.10
e		5.44BSC	
L	19.72	19.92	20.12
L1	4.03	4.13	4.23
θ1	5°	7°	9°
θ2	1°	2°	3°
θ3	4°	5°	6°
θ4	13°	15°	17°
ΦP1	3.50	3.60	3.70
ΦP2	7.09	7.19	7.29
ΦP3	2.40	2.50	2.60
Q1	2.31	2.41	2.51
S	6.05	6.15	6.25
R	0.30	0.40	0.50

（单位：mm）

Notice

MOSPEC reserves the rights to make changes of the content herein the document anytime without notification. MOSPEC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies. Please refer to MOSPEC website for the last document.

MOSPEC disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially incurred.

Application shown on the herein document are examples of standard use and operation. Customers are responsible for comprehending suitable use in particular applications. MOSPEC makes no representation or warranty that such application will be suitable for the specified use without further testing or modification.

The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by MOSPEC for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of MOSPEC or others.

These MOSPEC products are intended for usage in general electronic equipment. Please make sure to consult with MOSPEC before you use these MOSPEC products in equipment which require specialized quality and/or reliability, and in equipment which could have major impact to the welfare of human life (atomic energy control, aeronautics , traffic control, combustion control, safety devices etc.)