-30V P-Channel Enhancement Mode Power MOSFET

DESCRIPTION：

·Advanced Trench Technology


·Excellent $R_{DS(ON)}$ and Low Gate Charge

·Lead free product is acquired

·100% UIS Tested

·100% ΔVds Tested

V_{DS}	-30V
I_D	-11A
$R_{DS(ON)_MAX}$ @V_{GS}=-10V	16.5mΩ



SOP-8

TYPICAL APPLICATIONS：

·PWM Applications

·Load Switch

·Power Management

MAXIMUM RATINGS (at T_C = 25 °C, unless otherwise specified)

Characteristic	Symbol	Value	Unit
Drain-Source Voltage	V_{DSS}	-30	V
Gate-Source Voltage	V_{GSS}	±20	V
Continuous Drain Current TC = 25℃ TC = 100℃	I_D	-11 -7	A
Pulsed Drain Current，tp<10us(1)	I_{DM}	-44	A
Single Pulsed Avalanche Energy(2)	E_{AS}	64	mJ
Power dissipation	P_D	3.1	W
Junction & Storage temperature Range	T_J, T_{STG}	-55~+150	℃

Notes： 1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature.
2. EAS condition: TJ=25℃, VDD= -15V, VG= -10V, RG=25Ω, L=0.5mH, IAS= -16A

THERMAL CHARACTERISTICS

Characteristic	Condition	Symbol	Value	Unit
Thermal resistance,	Junction to Ambient	$R_{\theta JA}$	40	℃/W

ELECTRICAL CHARATERISTICS (at T_J = 25 °C, unless otherwise specified)

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage VGS = 0V, ID = -250uA	$V_{(BR)DSS}$	-30			V
Zero Gate Voltage Drain Current VDS = -30 V, VGS = 0 V	I_{DSS}			-1	uA
Gate-Source Leakage Current VGS = ±20V, VDS = 0V	I_{GSS}			±100	nA
Gate-Source threshold voltage VDS = VGS, ID = -250uA	$V_{GS(th)}$	-1.0	-1.5	-2.5	V
Drain-Source On-State Resistance VGS = -10V, ID = -10A VGS = -4.5V, ID = -5A	$R_{DS(on)}$		12.7 17	16.5 24	mΩ
Input capacitance f=1MHz, VDS=-15 V, VGS=0 V	C_{iss}		2130		pF
Output capacitance f=1MHz, VDS=-15 V, VGS=0 V	C_{oss}		280		pF
Reverse transfer capacitance f=1MHz, VDS=-15 V, VGS=0 V	C_{rss}		252		pF
Total Gate Charge VDS=-15 V, VGS=-10V, ID = -5A	Qg		40		nC
Gate-Source Charge VDS=-15 V, VGS=-10V, ID = -5A	Qgs		7		nC
Gate-Drain(“Miller”) Charge V VDS=-15 V, VGS=-10V, ID = -5A	Qgd		8		nC
Turn-on delay time VDD= -15V, ID = -10A , VGS=-10V, RG=2.4Ω	$t_{d\ (ON)}$		10		ns
Rise time VDD= -15V, ID = -10A , VGS=-10V, RG=2.4Ω	tr		60		ns
Turn-off delay time VDD= -15V, ID = -10A , VGS=-10V, RG=2.4Ω	$t_{d\ (OFF)}$		52		ns
Fall time VDD= -15V, ID = -10A , VGS=-10V, RG=2.4Ω	tf		72		ns
Maximum Continuous Drain to Source Diode Forward Current	I_S			-11	A
Maximum Pulsed Drain to Source Diode Forward Current	I_{SM}			-44	A
Diode Forward Voltage VGS = 0V, IS =- 11A	V_{SD}		-0.8	-1.2	V

Typical Performance Characteristics




Figure 1. Output Characteristics




Figure 2. Typical Transfer Characteristics




Figure 3. On-resistance vs. Drain Current




Figure 4. Body Diode Characteristics




Figure 5. Gate Charge Characteristics




Figure 6. Capacitance Characteristics

Typical Performance Characteristics




Figure 7. Normalized Breakdown Voltage vs. Junction Temperature




Figure 8. Normalized on Resistance vs. Junction Temperature




Figure 9. Maximum Safe Operating Area




Figure 10. Maximum Continuous Drain Current vs. Case Temperature






Figure 11. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient

·Circuit diagram



·Package outlines : Dimensions in (mm)



SYMBOL	MIN	NOM	MAX
A	1.40	1.60	1.80
A1	0.05	0.15	0.25
A2	1.35	1.45	1.55
b	0.30	0.40	0.50
c	0.153	0.203	0.253
D	4.80	4.90	5.00
E	3.80	3.90	4.00
E1	5.80	6.00	6.20
L	0.45	0.70	1.00
θ	2°	4°	6°
L1	1.04 REF		
e	1.27 BSC		
R1	0.07 TYP		
R2	0.07 TYP		

Notice

MOSPEC reserves the rights to make changes of the content herein the document anytime without notification. MOSPEC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies. Please refer to MOSPEC website for the last document.

MOSPEC disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially incurred.

Application shown on the herein document are examples of standard use and operation. Customers are responsible for comprehending suitable use in particular applications. MOSPEC makes no representation or warranty that such application will be suitable for the specified use without further testing or modification.

The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by MOSPEC for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of MOSPEC or others.

These MOSPEC products are intended for usage in general electronic equipment. Please make sure to consult with MOSPEC before you use these MOSPEC products in equipment which require specialized quality and/or reliability, and in equipment which could have major impact to the welfare of human life (atomic energy control, aeronautics , traffic control, combustion control, safety devices etc.)