MOSPEC

232N85L

85V N-Channel Power MOSFET

V_{DSS}	85V
I_D @V_{GS}=10V	232A
$R_{DS(ON)_Typ.}$ @V_{GS}=10V	2.3mΩ

DESCRIPTION：

·Low On-Resistance

·Excellent FoM (figure of merit)


·100% ΔVDS & UIS & Rg Tested

TYPICAL APPLICATIONS：

·Green Molding Compound

·Moisture Sensitivity: Level 1 per J-STD-020

·UL Flammability Classification Rating 94V-0



TO-262

MAXIMUM RATINGS (at T_C = 25 °C, unless otherwise specified)

Characteristic	Condition	Symbol	Value	Unit
Drain - Source Voltage		V_{DS}	85	V
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current(1)	Tc=25℃ Tc=100℃	I_D	232 147	A
Pulsed Drain Current (2)		I_{DM}	929	A
Single Pulsed Avalanche Energy (3)		E_{AS}	1300	mJ
Single Pulse Avalanche Current	L= 10.0mH	I_{AS}	94	A
Power dissipation	Tc=25℃ Tc=100℃	P_D	227 91	W
Junction & Storage temperature Range		T_J, T_{STG}	-55~+150	℃

Notes： 1. This current is chip limited, which is calculated based on Rthjc..

2. This current is calculated on single pulse with 10μs Pulse

3. Defined by design, not subject to production test, EAS condition: TJ=25°C, VDD=50V, VGS=10V, L=1.0mH.

THERMAL CHARACTERISTICS

Characteristic	Condition	Symbol	Value	Unit
Thermal resistance,	Junction to Ambient Junction to Case	$R_{\theta JA}$ $R_{\theta JC}$	34 0.55	℃/W

ELECTRICAL CHARATERISTICS (at T_J = 25 °C, unless otherwise specified)

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage VGS = 0V, ID = 250uA	$V_{(BR)DSS}$	85			V
Zero Gate Voltage Drain Current VDS = 85 V, VGS = 0 V ,Tj=25℃ VDS = 85 V, VGS = 0 V ,Tj=125℃	I_{DSS}			1.0 100	uA
Gate-Source Leakage Current VGS = ±20V, VDS = 0V	I_{GSS}			±100	nA
Gate-Source threshold voltage VDS = VGS, ID = 250uA	$V_{GS(th)}$	2.0	3.0	4.0	V
Drain-Source On-State Resistance VGS = 10V, ID = 20A	$R_{DS(on)}$		2.3	2.8	mΩ
Forward Transconductance VDS = 5.0V, ID = 20A	gfs		55		S
Diode Forward Voltage VGS = 0V, I_{SD} =2.0A	V_{SD}		0.7	1.2	V
Gate Resistance f=1MHz	R_g		1.6		Ω
Input capacitance f=1MHz, VDS=40 V, VGS=0 V	C_{iss}		7223		pF
Output capacitance f=1MHz, VDS=40 V, VGS=0 V	C_{oss}		1443		pF
Reverse transfer capacitance f=1MHz, VDS=40 V, VGS=0 V	C_{rss}		44		pF
Turn-on delay time VDS=40 V, ID=20A, VGS=10V, R_{GEN}=3.0Ω	td (ON)		20		ns
Rise time VDS=40 V, ID=20A, VGS=10V, R_{GEN}=3.0Ω	tr		35		ns
Turn-off delay time VDS=40 V, ID=20A, VGS=10V, R_{GEN}=3.0Ω	td (OFF)		54		ns
Fall time VDS=40 V, ID=20A, VGS=10V, R_{GEN}=3.0Ω	tf		30		ns
Total Gate Charge VDS= 40V, ID= 20A, VGS= 10V VDS= 40V, ID= 20A, VGS= 6.0V	Q_G		100 64		nC
Gate to Source Charge VDS= 40V, ID= 20A, VGS= 10V	Q_{GS}		32		nC
Gate to Drain Charge VDS= 40V, ID= 20A, VGS= 10V	Q_{GD}		22		nC
Gate Plateau Voltage VDS= 40V, ID= 20A, VGS= 10V	$V_{plateau}$		4.9		nC
Revers Recovery Time I_F =20A, di_F/dt = 100A/us ,Tj=25℃	Trr		68		ns
Revers Recovery Charge I_F =20A, di_F/dt = 100A/us ,Tj=25℃	Qrr		152		uC
Peak Reverse Recovery Current Tc=25℃	IS			232	A

Typical Performance Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Gate-Source Voltage




Figure 4. On-Resistance vs. Drain Current and Gate Voltage




Figure 5. On-Resistance vs. Junction Temperature




Figure 6. Source-Drain Diode Forward Voltage




Figure 7. Gate Threshold Variation vs. Junction Temperature




Figure8. Gate Charge Characteristics




Figure 9. Capacitance Characteristics




Figure 10. Power Derating




Figure 11. Current Derating




Figure 12. Safe Operating Area







Figure 13. Normalized Maximum Transient Thermal Impedance

·Circuit diagram



·Package outlines : Dimensions in (mm)





DIM	MILLIMETERS	
	MIN	MAX
A	4.44	4.70
A1	2.54	2.79
b	0.70	0.90
b2	1.20	1.45
C2	1.14	1.40
D	8.51	8.89
E	10.00	10.40
e	2.54BSC	
L	13.46	14.00
L1	1.00	1.65
L2	3.56	3.71

Notice

MOSPEC reserves the rights to make changes of the content herein the document anytime without notification. MOSPEC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies. Please refer to MOSPEC website for the last document.

MOSPEC disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially incurred.

Application shown on the herein document are examples of standard use and operation. Customers are responsible for comprehending suitable use in particular applications. MOSPEC makes no representation or warranty that such application will be suitable for the specified use without further testing or modification.

The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by MOSPEC for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of MOSPEC or others.

These MOSPEC products are intended for usage in general electronic equipment. Please make sure to consult with MOSPEC before you use these MOSPEC products in equipment which require specialized quality and/or reliability, and in equipment which could have major impact to the welfare of human life (atomic energy control, aeronautics , traffic control, combustion control, safety devices etc.)