600V N-Channel Power MOSFET

V_{DSS}	600V
I_D	47A
$R_{DS(ON)_Typ.}$ @V_{GS}=10V	0.077Ω

DESCRIPTION：

·Very low FOM $R_{DS(on)}$×Qg

·Ultra-fast body diode

·100% avalanche tested

·Easy to use/drive

·RoHS compliant



TO-247-3L

TYPICAL APPLICATIONS：

·Switch Mode Power Supply (SMPS)

·Uninterruptible Power Supply (UPS)

·Power Factor Correction (PFC)

·LLC Half-bridge

·Charger

MAXIMUM RATINGS (at T_A = 25 °C, unless otherwise specified)

Characteristic	Condition	Symbol	Value	Unit
Continuous Drain Current	Tc=25℃ Tc=100℃	I_D	47 28.2	A
Pulsed Drain Current (1)		$I_{D\ pulse}$	141	A
Gate-Source Voltage		V_{GS}	±30	V
Single Pulsed Avalanche Energy (2)		E_{AS}	1160	mJ
Repetitive Avalanche Energy (2)		E_{AR}	1.76	mJ
Avalanche Current		I_{AR}	8.7	A
Power dissipation		P_D	391	W
Continuous Diode Forward Current		I_S	47	A
Diode Pulsed Current (1)		$I_{S\ pulse}$	141	A
Reverse Diode dv/dt		dv/dt	50	V/ns
Junction & Storage temperature Range		T_J, T_{STG}	-55~+150	℃

Notes： 1. Repetitive Rating: Pulse width limited by maximum junction temperature

2. I_{AS} = 8.7A, V_{DD} = 50V, R_G = 25Ω, Starting T_J = 25°C

THERMAL CHARACTERISTICS

Characteristic	Condition	Symbol	Value	Unit
Thermal resistance,	Junction to Ambient Junction to Case	$R_{\theta JA}$ $R_{\theta JC}$	62 0.32	℃/W

ELECTRICAL CHARATERISTICS (at T_J = 25 °C, unless otherwise specified)

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage VGS = 0V, ID = 250uA	$V_{(BR)DSS}$	600			V
Zero Gate Voltage Drain Current VDS = 600 V, VGS = 0 V ,Tj=25℃	I_{DSS}			5	uA
Gate-Source Leakage Current VGS = ±30V, VDS = 0V	I_{GSS}			±100	nA
Gate-Source threshold voltage VDS = VGS, ID = 250uA	$V_{GS(th)}$	3		5	V
Drain-Source On-State Resistance VGS = 10V, ID = 24A	$R_{DS(on)}$		0.077	0.09	Ω
Gate Resistance f=1MHz	Rg		0.8		Ω
Input capacitance f=1MHz, VDS=100 V, VGS=0 V	C_{iss}		3685		pF
Output capacitance f=1MHz, VDS=100 V, VGS=0 V	C_{oss}		134		pF
Reverse transfer capacitance f=1MHz, VDS=100 V, VGS=0 V	C_{rss}		3.1		pF
Total Gate Charge VDS= 480V, ID= 47A,VGS= 10V	Q_G		78		nC
Gate to Source Charge VDS= 480V, ID= 47A,VGS= 10V	Q_{GS}		24		nC
Gate to Drain Charge VDS= 480V, ID= 47A,VGS= 10V	Q_{GD}		30		nC
Turn-on delay time VDD=400 V, ID=47A, R_{GEN}=25Ω	td (ON)		49		ns
Rise time VDD=400 V, ID=47A, R_{GEN}=25Ω	tr		123		ns
Turn-off delay time VDD=400 V, ID=47A, R_{GEN}=25Ω	td (OFF)		105		ns
Fall time VDD=400 V, ID=47A, R_{GEN}=25Ω	tf		49		ns
Diode Forward Voltage VGS = 0V, I_{SD} =24A	V_{SD}		1.0	1.5	V
Revers Recovery Time V_R=400V, I_F=23A, di_F/dt = 100A/us	Trr		170		ns
Revers Recovery Charge V_R=400V, I_F=23A, di_F/dt = 100A/us	Qrr		1.05		uC
Peak Reverse Recovery Current V_R=400V, I_F=23A, di_F/dt = 100A/us	Irrm		12.4		A

Typical Performance Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current




Figure 4. Capacitance




Figure 5. Gate Charge




Figure 6. Body Diode Forward Voltage




Figure 7. On-Resistance vs.Temperature




Figure8. Breakdown voltage vs. Junction Temperature




Figure 9. Transient Thermal Impedance




Figure 10. Safe Operation Area






Figure 11. Typ. Coss Stored Energy

·Circuit diagram



·Package outlines :



Unit:mm			
Symbol	Min.	Nom	Max.
A	4.80	5.00	5.20
A1	2.21	2.41	2.61
A2	1.85	2.00	2.15
b	1.11	1.21	1.36
b2	1.91	2.01	2.21
b4	2.91	3.01	3.21
c	0.51	0.61	0.75
D	20.70	21.00	21.30
D1	16.25	16.55	16.85

Unit:mm			
Symbol	Min.	Nom.	Max.
E	15.50	15.80	16.10
E1	13.00	13.30	13.60
E2	4.80	5.00	5.20
E3	2.30	2.50	2.70
e	5.44BSC		
L	19.62	19.92	20.22
L1	-	-	4.30
ΦP	3.40	3.60	3.80
ΦP1	-	-	7.30
S	6.15BSC		

Notice

MOSPEC reserves the rights to make changes of the content herein the document anytime without notification. MOSPEC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies. Please refer to MOSPEC website for the last document.

MOSPEC disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially incurred.

Application shown on the herein document are examples of standard use and operation. Customers are responsible for comprehending suitable use in particular applications. MOSPEC makes no representation or warranty that such application will be suitable for the specified use without further testing or modification.

The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by MOSPEC for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of MOSPEC or others.

These MOSPEC products are intended for usage in general electronic equipment. Please make sure to consult with MOSPEC before you use these MOSPEC products in equipment which require specialized quality and/or reliability, and in equipment which could have major impact to the welfare of human life (atomic energy control, aeronautics , traffic control, combustion control, safety devices etc.)