

## 100V N-Channel Power MOSFET


### DESCRIPTION :

- Excellent  $R_{DS(ON)}$
- Low Gate Charge
- 100% UIS Tested, 100%  $\Delta V_{DS}$  Tested
- RoHS compliant
- Halogen Free

### TYPICAL APPLICATIONS :

- Power Management
- Load Switch
- PWM Application

$V_{DSS}$	100V
$I_D$	80A
$R_{DS(ON)_{MAX}}$ @ $V_{GS}=10V$	4.4m $\Omega$



ITO-220AB

### MAXIMUM RATINGS (at $T_C = 25^\circ\text{C}$ , unless otherwise specified)

Characteristic	Condition	Symbol	Value	Unit
Drain-Source Voltage		$V_{DS}$	100	V
Gate-Source Voltage		$V_{GS}$	$\pm 20$	V
Continuous Drain Current	$T_C=25^\circ\text{C}$ $T_C=100^\circ\text{C}$	$I_D$	80 50	A
Pulsed Drain Current <sup>(1)</sup>		$I_{DM}$	Refer to Fig4	A
Single Pulsed Avalanche Energy <sup>(2)</sup>		$E_{AS}$	900	mJ
Power dissipation	$T_C=25^\circ\text{C}$ $T_C=100^\circ\text{C}$	$P_D$	63 25	W
Junction & Storage temperature Range		$T_J, T_{STG}$	-55~+150	$^\circ\text{C}$

Notes : 1. Repetitive Rating : Pulse Width Limited by Maximum Junction Temperature.

2.  $E_{AS}$  condition: Starting  $T_J=25^\circ\text{C}$ ,  $V_{DD}=50V$ ,  $V_G=10V$ ,  $R_G=25\text{ohm}$ ,  $L=3\text{mH}$ ,  $I_{AS}=24.5A$ ,  $V_{DD}=0V$  during time in avalanche.

### THERMAL CHARACTERISTICS

Characteristic	Condition	Symbol	Value	Unit
Thermal resistance,	Junction to Ambient Junction to Case	$R_{\theta JA}$ $R_{\theta JC}$	57 2.0	$^\circ\text{C}/W$

ELECTRICAL CHARACTERISTICS (at  $T_J = 25\text{ }^\circ\text{C}$ , unless otherwise specified)

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage $V_{GS} = 0V, I_D = 250\mu A$	$V_{(BR)DSS}$	100			V
Zero Gate Voltage Drain Current $V_{DS} = 80V, V_{GS} = 0V$	$I_{DSS}$			1.0	$\mu A$
Gate-Source Leakage Current $V_{GS} = \pm 20V, V_{DS} = 0V$	$I_{GSS}$			$\pm 100$	nA
Gate-Source threshold voltage $V_{DS} = V_{GS}, I_D = 250\mu A$	$V_{GS(th)}$	2.1	3.0	3.9	V
Drain-Source On-State Resistance $V_{GS} = 10V, I_D = 20A$	$R_{DS(on)}$		4.4	5.4	m $\Omega$
Input capacitance $f=1MHz, V_{DS}=50V, V_{GS}=0V$	$C_{iss}$		6165	8632	pF
Output capacitance $f=1MHz, V_{DS}=50V, V_{GS}=0V$	$C_{oss}$		858	1202	pF
Reverse transfer capacitance $f=1MHz, V_{DS}=50V, V_{GS}=0V$	$C_{rss}$		20	41	pF
Gate Resistance $f=1MHz$	$R_g$		2.3		$\Omega$
Total Gate Charge $V_{DS}= 50V, I_D= 20A, V_{GS}= 0$ to 10V	$Q_G$		87	117	nC
Gate to Source Charge $V_{DS}= 50V, I_D= 20A, V_{GS}= 0$ to 10V	$Q_{GS}$		34	46	nC
Gate to Drain Charge $V_{DS}= 50V, I_D= 20A, V_{GS}= 0$ to 10V	$Q_{GD}$		17	22	nC
Turn-on delay time $V_{DD}=50V, V_{GS}= 10V, I_D= 20A, R_{GEN}=6.2\Omega$	$t_{d(ON)}$		29		ns
Rise time $V_{DD}=50V, V_{GS}= 10V, I_D= 20A, R_{GEN}=6.2\Omega$	$t_r$		41		ns
Turn-off delay time $V_{DD}=50V, V_{GS}= 10V, I_D= 20A, R_{GEN}=6.2\Omega$	$t_{d(OFF)}$		68		ns
Fall time $V_{DD}=50V, V_{GS}= 10V, I_D= 20A, R_{GEN}=6.2\Omega$	$t_f$		35		ns

## Body Diode

ELECTRICAL CHARACTERISTICS (at  $T_J = 25\text{ }^\circ\text{C}$ , unless otherwise specified)

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Diode Forward Voltage $V_{GS} = 0V, I_S = 20A$	$V_{SD}$			1.2	V
Maximum Continuous Body Diode Forward Current	$I_S$			80	A
Maximum Pulsed Body Diode Forward Current	$I_{SM}$			318	A
Revers Recovery Time $I_F = 20A, di/dt = 100A/\mu s$	$T_{rr}$	55	77	107	ns
Revers Recovery Charge $I_F = 20A, di/dt = 100A/\mu s$	$Q_{rr}$		183		nC

Typical Performance Characteristics




Figure 1. Power De-rating




Figure 2. Current De-rating




Figure 3. Normalized Maximum Transient Thermal Impedance




Figure 4. Peak Current Capacity




Figure 5. Output Characteristics




Figure 6. Typical Transfer Characteristics




Figure 7. On-resistance vs. Drain Current




Figure 8. Body Diode Characteristics




Figure 9. Gate Charge Characteristics




Figure 10. Capacitance Characteristics




Figure 11. Normalized Breakdown voltage vs. Junction Temperature




Figure 12. Normalized on Resistance vs. Junction Temperature




Figure 13. Normalized Threshold Voltage vs. Junction Temperature




Figure 14. R<sub>DS(ON)</sub> vs. V<sub>GS</sub>






Figure 15. Maximum Safe Operating Area

- Circuit diagram



- Package outlines : Dimensions in (mm)



DIM	MILLIMETERS	
	MIN	MAX
A	14.80	16.10
B	12.65	14.40
C	9.70	10.36
D	4.60	6.80
E	2.50	3.50
F	0.90	1.55
G	0.90	1.55
H	0.50	0.90
I	2.40	2.70
J	2.34	3.30
K	0.55	1.30
L	0.36	0.80
M	4.20	4.90
N	1.10	1.80
O	2.90	3.50
P	2.30	3.15
Q	2.90	3.50
R	2.80	4.85

## Notice

MOSPEC reserves the rights to make changes of the content herein the document anytime without notification. MOSPEC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies. Please refer to MOSPEC website for the last document.

MOSPEC disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially incurred.

Application shown on the herein document are examples of standard use and operation. Customers are responsible for comprehending suitable use in particular applications. MOSPEC makes no representation or warranty that such application will be suitable for the specified use without further testing or modification.

The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by MOSPEC for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of MOSPEC or others.

These MOSPEC products are intended for usage in general electronic equipment. Please make sure to consult with MOSPEC before you use these MOSPEC products in equipment which require specialized quality and/or reliability, and in equipment which could have major impact to the welfare of human life ( atomic energy control, aeronautics , traffic control, combustion control, safety devices etc.)